



6.2 Axerstulp

6.2.1 Bandseite E5 / A

6.2.1.1 Grundsicherheit – RC1 N



					 #			Nº
J	290 – 410	300	120	150	–	–	Roto Sil	260201
	411 – 600	490	190	250	–	–	Roto Sil	256024
	601 – 800	690	200	350	–	–	Roto Sil	260204
	801 – 1.000	890	200	500	–	–	Roto Sil	260205
		890	200	500	1	E	Roto Sil	260208
	1.001 – 1.200	1.090	200	500	–	–	Roto Sil	260209
		1.090	200	500	1	E	Roto Sil	260212
1.201 – 1.400	1.290	200	500	1	E	Roto Sil	260215	
N	290 – 410	300	120	150	–	–	Roto Sil	288150
	411 – 600	490	190	250	–	–	Roto Sil	284217
	601 – 800	690	200	350	–	–	Roto Sil	284218
	801 – 1.000	890	200	500	1	E	Roto Sil	284219
	1.001 – 1.200	1.090	200	500	1	E	Roto Sil	284216
	1.201 – 1.400	1.290	200	500	1	E	Roto Sil	286496



INFO

Ab FFB 1400 mm Zweitschere erforderlich.



INFO

Axerstulp ohne Sperre benötigt zusätzlich Schaltsperre oder Lüfterschere.